

Choice of the World's top DX'ers

Covering HF and 6 meters the FT-DX9000 Series answers the call for the ultimate DX base station.



FT DX 9000MP

No other Amateur transceiver offers you 400 Watts of transmitter power for the biggest, cleanest voice on the bands. And switching to Class-A operation at 100 Watts of output, you enjoy the benefits of ultra low distortion others can't match at 100 Watts! Two pairs of Meters, plus LCD Window; Data Management Unit and Flash Memory Slot Built In. Main/Sub Receiver VRF, plus Full Dual Receive Capability, External 50V/24 A Switching Regulator Power Supply and Speaker with Audio Filters.

FT DX 9000D

The "Fully loaded" model represents the total FT DX 9000 experience. Included is the large TFT display, along with 1.8-14 MHz high-Q "μ" front-end RF tuning circuit, utilizing a large-diameter 1.1" (28mm) ferrite core and precision motor drive. Its Q of over 300 provides razor-sharp RF tuning-ideal for today's crowded bands! Large TFT, Data Management Unit and Flash Memory Slot Built In. Main/Sub Receiver VRF, plus Full Dual Receive Capability, Three μ-Tuning Modules for 160 - 20 M, 50 V/12 A Internal Switching Regulator Power Supply.



FT DX 9000 Contest

The FT DX 9000 gives you the opportunity to build up your radio to match your operating style and competitive requirements. World-class ergonomics combine with leading-edge performance to put more QSOs in your log faster. This is what Amateur Radio is about: building the best, so you can be your best! Two Pairs of Meters, plus LCD Window, VRF Input Preselector Filter, Three Key Jacks, and Dual Headphone Jacks, 50 V/12 A Internal Switching Regulator Power Supply.



FT-2000, FT-2000D, FT-950 and the FT-450D



FT-2000 and FT-2000D

This rugged DX hunter has power and performance to spare. The FT-2000 provides a full 100 Watts RF output on 160 through 6 meters with an internal power supply, but the FT-2000D version doubles down with 200 Watts and an external supply. The impressive feature list for both versions includes dual receive capability for effortless split frequency operation; a receiver front-end VRF (Variable RF Tuning) preselector; 1st IF roofing filters (3/6/15 kHz) for superb dynamic range; variable IF bandwidth and IF Shift; receiver DSP with Auto-Notch, Manual Notch, Digital Noise Reduction; and a continuously-variable passband contour control.

Vertex Standard U.S.A. Inc.
6125 Phyllis Drive, Cypress, CA 90630
(714) 827-7600
<http://www.yaesu.com>

FT DX 5000 Series

The FT DX 5000 Series HF/50 MHz 200 Watt Transceivers are a premium Class of Yaesu radios with 2 Independent Receivers plus many options and accessories designed for the serious DXer.

With 112 dB dynamic range and an IP3 [3rd Order Intercept Point] of +40 dBm (CW, 500 Hz BW), you'll find extra sharp roofing filters for VFOA/Main receiver are selectable between 300 Hz (optional on some versions), 600 Hz, 3 kHz, 6 kHz and 15 kHz.

Three electro-luminescent sub-displays indicate sub frequency, graphical wave and menu functions. Additional features: Parametric Microphone Equalizer; Dual Receive In Band Function Contest-ready Antenna Selection; Manual and Automatic Digital Notch; High Speed Automatic Antenna Tuner; DSP Noise Reduction.



FT DX 5000MP

Station Monitor SM-5000 included; 0.05 ppm OCXO included; 300 Hz Roofing Filter included

FT DX 5000D

Station Monitor SM-5000 included; 0.5 ppm TCXO included; 300 Hz Roofing Filter optional

FT DX 5000

Station Monitor SM-5000 optional; 0.5 ppm TCXO included; 300 Hz Roofing Filter optional

FT-950



Whether you're a serious or casual DXer, the Yaesu FT-950 should be at the top of your list. The FT-950 packs a 100 watt punch on 160 through 6 meters and includes a built-in antenna tuner; triple-conversion superheterodyne receiver; three factory-installed 1st IF roofing filters; variable IF bandwidth and IF shift, manual IF notch filter, an Automatic Digital Notch Filter (DNF) and many other expanded features available with optional DMU-2000 Data Management Unit.

FT-450D



This easy-to-pack radio is a DXpeditioner's dream come true - a lightweight, high performance transceiver spanning 160 through 6 meters with 100 Watts RF output. When it's time to wade into the pileups, you'll appreciate the FT-450D's 10 kHz bandwidth roofing filter in the 68 MHz first IF, right after the first mixer. This filter provides outstanding selectivity when the going gets rough - a feature rarely found in rigs in this price range!